

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET	
PRODUCT NAME	FAST YELLOW G-B
CHEMICAL NATURE	MONO AZO
CHEMICAL FORMULAR	C ₁₇ H ₁₆ N ₄ O ₄
COLOR INDEX NAME	PIGMENT YELLOW 1 (11680)
CAS NO.	2512-29-0
STRENGTH	100±2%
<u>PHYS</u>	ICAL PROPERTIES
PH AQUEOUS EXTRACT	7.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	<u>≤2.0%</u>
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.45g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
FAST	NESS PROPERTIES
LIGHT FASTNESS	6
HEAT FASTNESS	160°C
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
TECHNICAL PROPERTIES	
Greenish shade, high glossy, high tinting strength.	
A	APPLICATION
It's mainly used for water based decorat	ive paint and industrial paint.
Suggested for coil coating, textile printing and solvent based decorative paint.	
NOTE	
The above information is provided as guidelines	for your reference only. The accurate effects should be based on
the test results in laboratory.	