

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

| TECHNICAL DATA SHEET | |
|---|--|
| PRODUCT NAME | PERMANENT YELLOW GR-W |
| CHEMICAL NATURE | DISAZO |
| CHEMICAL FORMULAR | $C_{36}H_{34}Cl_2N_6O_4$ |
| COLOR INDEX NAME | PIGMENT YELLOW 13 (21100) |
| CAS NO. | 5102-83-0 |
| STRENGTH | 100±2% |
| PHYS | SICAL PROPERTIES |
| PH AQUEOUS EXTRACT | 6.0-7.0 |
| RESIDUE ON SIEVE (100 um) | ≤3.0% |
| WATER SOLUBLE MATTER | ≤2.0% |
| SOLUBLE IN WATER | INSOLUBLE |
| ODOUR | NONE |
| PHYSICAL FORM | DRY YELLOW POWDER |
| SPECIFIC GRAVITY | 1.40g/cm ³ |
| OIL ABSORPTION | ≤45g/100g |
| VOLATILE AT 105°C | <3.0% |
| FAST | NESS PROPERTIES |
| LIGHT FASTNESS | 5 |
| HEAT FASTNESS | 160 °C |
| WATER RESISTANCE | 5 |
| OIL RESISTANCE | 4 |
| ACID RESISTANCE | 5 |
| ALKALI RESISTANCE | 5 |
| TECHNICAL PROPERTIES | |
| Reddish shade, semi-transparent. | |
| | APPLICATION |
| It's mainly used for water-based ink, textile printing. | |
| Suggested for general use. | |
| | <u>NOTE</u> |
| The above information is provided as guidelines | s for your reference only. The accurate effects should be based on |
| the test results in laboratory. | |