Loval Chemical

the test results in laboratory.

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

| PRODUCT NAME | PERMANENT YELLOW 5GF-B |
|--|---|
| CHEMICAL NATURE | DISAZO |
| CHEMICAL FORMULAR | C ₃₄ H ₃₀ Cl ₂ N ₆ O ₄ |
| COLOR INDEX NAME | PIGMENT YELLOW 14 (21095) |
| CAS NO. | 5468-75-7 |
| STRENGTH | 100±2% |
| PHYSICAL PROPERTIES | |
| PH AQUEOUS EXTRACT | 6.5 |
| RESIDUE ON SIEVE (100 um) | ≤3.0% |
| WATER SOLUBLE MATTER | ≤2.0% |
| SOLUBLE IN WATER | INSOLUBLE |
| ODOUR | NONE |
| PHYSICAL FORM | DRY YELLOW POWDER |
| SPECIFIC GRAVITY | 1.46g/cm ³ |
| OIL ABSORPTION | ≤45g/100g |
| VOLATILE AT 105℃ | <3.0% |
| FASTNESS PROPERTIES | |
| LIGHT FASTNESS | 6 |
| HEAT FASTNESS | 180℃ |
| WATER RESISTANCE | 5 |
| OIL RESISTANCE | 5 |
| ACID RESISTANCE | 5 |
| ALKALI RESISTANCE | 5 |
| TECHNICAL PROPERTIES | |
| Greenish shade, high opaque. | |
| <u>APPLICATION</u> | |
| It's mainly used for PP Inks, NC inks, UV inks, PA inks. | |
| Suggested for toluene-base inks. | |
| <u>NOTE</u> | |
| The above information is provided as guidelines for your reference only. The accurate effects should be based on | |