Laval Chemica

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

TECHNICIE DITTISHEET	
PRODUCT NAME	PERMANENT YELLOW 5GF-A
CHEMICAL NATURE	DISAZO
CHEMICAL FORMULAR	C ₃₄ H ₃₀ Cl ₂ N ₆ O ₄
COLOR INDEX NAME	PIGMENT YELLOW 14 (21095)
CAS NO.	5468-75-7
STRENGTH	100±2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	6.0-7.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.46g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
FASTNESS PROPERTIES	
LIGHT FASTNESS	6
HEAT FASTNESS	180℃
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
TECHNICAL PROPERTIES	
Greenish shade, semi-transparent.	

Greenish shade, semi-transparent.

APPLICATION

It's mainly used for offset inks, water-based inks, textile printing and PVC EVA, PE. Suggested for PA inks, NC inks, PP inks, water-based decorative paint, solvent-based decorative paint.

NOTE

The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.