

the test results in laboratory.

## HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

## TECHNICAL DATA SHEET

TECHNICIE DITTIONEE	
PRODUCT NAME	FAST YELLOW RN
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{18}H_{18}N_4O_6$
COLOR INDEX NAME	PIGMENT YELLOW 65 (11740)
CAS NO.	6528-34-3
STRENGTH	100 <u>+</u> 2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	6.0-8.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.30g/cm <sup>3</sup>
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
<u>FASTNESS PROPERTIES</u>	
LIGHT FASTNESS	7
HEAT FASTNESS	210℃
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
TECHNICAL PROPERTIES	
Reddish shade, easy dispersing, good heat resistance, high covering power.	
<u>APPLICATION</u>	
It's mainly used for road marking paint.	
<u>NOTE</u>	

The above information is provided as guidelines for your reference only. The accurate effects should be based on