

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TEC	HNICAL DATA SHEET
PRODUCT NAME	PERMANENT YELLOW HR-05
CHEMICAL NATURE	DISAZO
CHEMICAL FORMULAR	C ₃₆ H ₃₂ Cl ₄ N ₆ O ₈
COLOR INDEX NAME	PIGMENT YELLOW 83 (21108)
CAS NO.	5567-15-7
STRENGTH	100±2%
PH	IVSICAL PROPERTIES
PH AQUEOUS EXTRACT	6.5
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.50g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
FA	STNESS PROPERTIES
LIGHT FASTNESS	7
HEAT FASTNESS	200°C
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
TEC	CHNICAL PROPERTIES
Reddish shade, high transparent, low	viscosity, high glossy.
	APPLICATION
It's main used for solvent-based indus	strial paint, decorative paint.
Suggested for PA ink, NC ink, PP ink.	
	NOTE
The above information is provided as guideling	nes for your reference only. The accurate effects should be based on
the test results in laboratory.	