



Loyal Chemical

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299

Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

PRODUCT NAME	PERMANENT YELLOW FGL
CHEMICAL NATURE	MONOAZO
CHEMICAL FORMULAR	$C_{26}H_{27}ClN_4O_8S$
COLOR INDEX NAME	PIGMENT YELLOW 97 (11767)
CAS NO.	12225-18-2
STRENGTH	100 \pm 2%
<u>PHYSICAL PROPERTIES</u>	
PH AQUEOUS EXTRACT	7.0-8.0
RESIDUE ON SIEVE (100 μ m)	\leq 3.0%
WATER SOLUBLE MATTER	\leq 2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.40g/cm ³
OIL ABSORPTION	\leq 45g/100g
VOLATILE AT 105 $^{\circ}$ C	$<$ 3.0%
<u>FASTNESS PROPERTIES</u>	
LIGHT FASTNESS	7
HEAT FASTNESS	200 $^{\circ}$ C
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
<u>TECHNICAL PROPERTIES</u>	
High covering power, good heat resistance, good solvent resistance.	
<u>APPLICATION</u>	
It's mainly used for all paint and PVC, Fiber, EVA, PP, PE. Suggested for PU, RUB and OEM paint.	
<u>NOTE</u>	
The above information is provided as guidelines for your reference only. The accurate effects should be based on the test results in laboratory.	