

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECI	HNICAL DATA SHEET
PRODUCT NAME	LITHOL FAST YELLOW 2R
CHEMICAL NATURE	ISOINDOLINE
CHEMICAL FORMULAR	C ₁₆ H ₉ N ₅ O ₆
COLOR INDEX NAME	PIGMENT YELLOW 139 (56298)
CAS NO.	36888-99-0
STRENGTH	100 <u>+</u> 2%
PH	IVSICAL PROPERTIES
PH AQUEOUS EXTRACT	5.0-6.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	<u>≤2.0%</u>
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	1.74g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105°C	<3.0%
FA	STNESS PROPERTIES
LIGHT FASTNESS	8
HEAT FASTNESS	200°C
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	5
ALKALI RESISTANCE	5
TEC	CHNICAL PROPERTIES
Greenish shade, transparent, high tin	iting strength.
	APPLICATION
It's mainly used for plastic, rubber, fi	ber, powder coating.
Suggested for powder coating.	
	<u>NOTE</u>
The above information is provided as guideling	nes for your reference only. The accurate effects should be based or
the test results in laboratory.	