

the test results in laboratory.

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

PRODUCT NAME	FAST YELLOW 4G
CHEMICAL NATURE	PYRIMIDINE
CHEMICAL FORMULAR	C ₃₄ H ₃₀ Cl ₂ N ₆ O ₄
COLOR INDEX NAME	PIGMENT YELLOW 150 (12764)
CAS NO.	25157-64-6
STRENGTH	100±2%
PHYSICAL PROPERTIES	
PH AQUEOUS EXTRACT	7.0-8.0
RESIDUE ON SIEVE (100 um)	≤3.0%
WATER SOLUBLE MATTER	≤2.0%
SOLUBLE IN WATER	INSOLUBLE
ODOUR	NONE
PHYSICAL FORM	DRY YELLOW POWDER
SPECIFIC GRAVITY	2.0g/cm ³
OIL ABSORPTION	≤45g/100g
VOLATILE AT 105℃	<3.0%
<u>FASTNESS PROPERTIES</u>	
LIGHT FASTNESS	8
HEAT FASTNESS	280°C
WATER RESISTANCE	5
OIL RESISTANCE	5
ACID RESISTANCE	4
ALKALI RESI <mark>STANC</mark> E	4
TECHNICAL PROPERTIES	
Greenish shade, high tinting strength.	
<u>APPLICATION</u>	
It's mainly used for plastic.	
Suggested for coating.	
<u>NOTE</u>	
The above information is provided as guidelines for your reference only. The accurate effects should be based on	