

the test results in laboratory.

HANGZHOU LOYAL CHEMICAL TECHNOLOGY CO., LTD.

Plant: Linjiang Industrial Park Xiaoshan District Hangzhou China

Office: 403, A Block, Nice Hi-Tech Park, 1117-2, Youyi Road, Guali Town, Xiaoshan, Hangzhou, China

Tel: +86 (0571) 82551299 Fax: +86 (0571) 82522228

TECHNICAL DATA SHEET

PRODUCT NAME	PERMANENT YELLOW LBE		
CHEMICAL NATURE	DISAZO		
CHEMICAL FORMULAR	C ₃₅ H ₃₂ CI ₂ N ₆ O ₄		
COLOR INDEX NAME	PIGMENT YELLOW 174 (20198)		
CAS NO.	78952-72-4		
STRENGTH	100±2%		
PHYSIC	CAL PROPERTIES		
PH AQUEOUS EXTRACT	6.0-7.0		
RESIDUE ON SIEVE (100 um)	≤3.0%		
WATER SOLUBLE MATTER	≤2.0%		
SOLUBLE IN WATER	INSOLUBLE		
ODOUR	NONE		
PHYSICAL FORM	DRY YELLOW POWDER		
SPECIFIC GRAVITY	1.31g/cm ³		
OIL ABSORPTION	≤45g/100g		
VOLATILE AT 105℃	<3.0%		
FASTN	ESS PROPERTIES		
LIGHT FASTNESS	6		
HEAT FASTNESS	190℃		
WATER RESISTANCE	4		
OIL RESISTANCE	5		
ACID RESISTANCE	5		
ALKALI RESISTANCE	5		
TECHNICAL PROPERTIES Reddish shade, high transparent, high glossy, high flow APPLICATION It's mainly used for offset ink, UV ink. NOTE			
		The above information is provided as guidelines for	or your reference only. The accurate effects should be based on